

Air Grinders



Air Grinders | Die Grinders

308B
Straight



- 0.25 kW
- 25,000 rpm
- Only 0.46 kg and 172 mm
- Contains: 1/4" and 6 mm collets

302B
Angle



- 0.25 kW
- 20,000 rpm
- Only 0.58 kg and 175 mm
- Contains: 1/4" and 6 mm collets

307B
Straight



- 0.19 kW
- 28,000 rpm
- Only 0.33 kg and 125 mm
- Contains: 1/4" and 6 mm collets

5102MAX
Angle



- 0.30 kW
- 20,000 rpm
- Only 0.64 kg and 178 mm
- Composite housing
- Contains: 1/4" and 6 mm collets

Also available
5108MAX
Straight



- 0.30 kW
- 20,000 rpm
- Only 0.64 kg and 178 mm
- Composite housing
- Contains: 1/4" and 6 mm collets

Ref.	CCN	mm	kW	rpm	kg	mm	in	mm	l/s	l/s	dB(A)	m/s ² /K ⁽¹⁾
308B	48488332	1/4" + 6	0.25	25,000	0.46	172	1/4 NPT	10	3.3	13.20	92.0	3.7/1.2
302B	48488365	1/4" + 6	0.25	20,000	0.58	175	1/4 NPT	10	2.8	10.80	90.0	5.5/1.5
307B	48488316	1/4" + 6	0.19	28,000	0.33	125	1/4 NPT	10	2.8	11.30	83.0	4.5/1.1

⁽¹⁾ ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.

Ref.	CCN	mm	kW	rpm	kg	mm	in	mm	l/s	l/s	dB(A)	m/s ² /K ⁽¹⁾
5102MAX	48488357	1/4" + 6	0.30	20,000	0.64	180	1/4 NPT	10	2.8	11.80	84.1	3.3/1.1
5108MAX	48488340	1/4" + 6	0.30	25,000	0.46	172	1/4 NPT	10	2.8	11.80	83.3	1.8/0.8

⁽¹⁾ ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.

Air Grinders | Die Grinders

301B Angle



- 0.19 kW
- 21,000 rpm
- Only 0.46 kg and 128 mm
- Contains: 1/4" and 6 mm collets

Replacement collets



Ref.	CCN	diameter
Collets for 301B, 302B, 307B, 308B, 5102MAX, 5108MAX and LA429-EU		
301-700C	80128952	Ø 1/8"
301-700B	04552600	Ø 6 mm
301-700	80102346	Ø 1/4"

LA429-EU Straight



- 0.42 kW
- 20,000 rpm
- Only 0.54 kg
- Contains: 1/4" and 6 mm collets

Air Grinders | Wheel Grinders

345MAX-M 125 mm (5")



- 0.66 kW
- 12,000 rpm
- Speed governor
- Composite housing
- Piped-away exhaust system

Also available
3445MAX-M
115 mm (4.5")

LA422-EU 125 mm (5")



- 0.50 kW
- 12,000 rpm

Also available
LA421-EU
100 mm (4")

Ref.	CCN	mm	kW	rpm	kg	mm	in	mm	l/s	l/s	dB(A)	m/s ² /K ⁽¹⁾
301B	48488308	1/4" + 6	0.19	21,000	0.46	128	1/4 NPT	10	2.8	11.30	91.8	5.9/1.0
LA429-EU	01328558	1/4" + 6	0.42	22,000	0.54	142	1/4 NPT	10	1.8	9.00	91.0	3.2/1.7

⁽¹⁾ ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.

Ref.	CCN	mm	mm	kW	rpm	kg	mm	in	mm	l/s	l/s	dB(A)	m/s ² /K ⁽¹⁾
345MAX-M	45664257	125	M14	0.66	12,000	1.56	245	1/4 NPT	10	4.9	19.30	79.6	7.9/0.7
3445MAX-M	45664240	115	M14	0.66	12,000	1.53	245	1/4 NPT	10	4.9	19.30	79.6	6.4/2.0
LA422-EU	01328582	125	3/8" – 24	0.50	12,000	1.75	229	1/4 NPT	10	2.8	10.40	85.6	6.0/2.1
LA421-EU	01328632	100	3/8" – 24	0.50	12,000	1.75	229	1/4 NPT	10	2.8	10.40	85.6	4.8/1.4

⁽¹⁾ ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.